

SKIMCOAT 113 WHITE

SMOOTH FINISH COAT, CEMENTITIOUS PLASTER

DESCRIPTION

SKIMCOAT 113 WHITE are economical finish coats for indoor use only. The product is a cement based plaster specially formulated for use on concrete surfaces pre-applied with SKIM-BASE 112 or other cement mortar, concrete, stone, Autoclaved aerated concrete (AAC), brick based surface.

SKIMCOAT 113 WHITE is suitable for walls and ceilings giving a fine and smooth surface. This product are supplied as pre-mixed dry plastering mortar, only need to mix with Water and the material is ready to use.

MIXING AND APPLICATION:

Surface Preparation

Substrate must be sound, clean and free from dust, loose particles and contamination such as oil, grease including form-oil compounds. Uneven surfaces should be grinded down or patched.



Mixing

Slowly mix the powder with 43%+- 1% clean water (approx 17Liter to 10 Liter per 40kg bag). Recommend to mix with electric stirrer.

Note: Do Not Mix with sand.

Mix Thoroughly until homogeneous, allow mixture to slake for 5 minutes then stir again for 2 minutes before use.

Application

Apply onto surface by manual or mechanical means in one or two layers. Level out with a steel trowel or spatula. Recommended application thickness 1-2mm per layer.

PRODUCT INFORMATION:

Color	White
Packing	40 kg Per bag
Shelf Life	6 Months (From production date)
Storage	Store in dry condition
Dry Bulk density	≥ 1200kg/m ³

PERFORMANCE DATA:

Compressive Strength EN 1015-11	≥ 4.0 N/mm ² CLASS CS III
Flexural Strength EN 1015-11	≥1.0 N/mm ²
Adhesion Strength EN 1015-12	0.5 N/mm ² *
Capillary Water Absorption EN 1015-18	PASS
Coverage	1 kg/m ² /mm (Approximately)
Thickness	1mm - 2mm
Pot Life	3 hours

* Bonding to the substrate depends very much on the substrate and might vary from the specified value. It is recommended to perform tests on site to verify the actual bonding with the substrate.



FEATURE

- FOR INDOOR ONLY
- 1mm to 2 mm thickness



PRODUCT SAFETY

Please refer to Safety Data Sheet.

The product is a cement-based product and may cause skin irritation. Avoid contact with skin by wearing suitable clothing and gloves. In the event of contact with skin, wash with clean water to minimize possible irritation. If any material gets into the eyes, wash immediately and repeatedly with eye-wash or clean water. If the irritation persist, seek medical treatment.

Manufacturer

Aalborg Portland Malaysia Sdn. Bhd. (275155-P)

Lot 75244, Pinji Estate, P.O. Box 428,

30750 Ipoh, Perak, Malaysia

www.aalborgportland.com.my

For more Information:

Unity Marketing (M) SDN. BHD.
www.unitymarketing.com.my



BUATAN MALAYSIA
MADE IN MALAYSIA

